

Economy Grade Carton Sealing BOPP TAPE Specification EN

TECHNICAL SHEET

Typical Applications

- Light weight carton sealing tape, suitable for manual dispenser application.
- Also for automated application.



Advantages and Benefits

- Good adhesion even in recycled cartons.
- Excellent tack.
- Long lasting adhesion
- Ideal for storage in extreme temperature conditions and high moisture environments once applied.



Construction

- Backing: Clear BOPP film.
- Adhesive: Natural rubber and hydrocarbon resins.
- Colour: Clear, white or brown adhesive.

TECHNICAL DATA

PP525	METRIC
Film Thickness	25 Micron
Total Thickness	42 Micron
Peel Adhesion	1,9 N/cm
Tensile Strength	38 N/cm
Elongation at break	130%
Application Temperature	2°C to 45°C
Service Temperature	-25°C to 65°C



Physical and performance characteristics shown above are obtained following tests recommended by AFERA and UBIS. The values given are typical values and do not constitute a specification. The user should determine whether the tape is suitable for the intended application.



PAKAVIMO PROCESŲ
OPTIMIZAVIMAS

STORAGE

Tape performance is guaranteed within the first 12 months. Product must be kept in its original box and in a dry atmosphere away from direct sunlight. For product traceability, please advise the 12 digit batch number printed on labels.

SECURITY

Product does not contain any dangerous or unhealthy components. Security data sheets are available based on directive 91/155/EC. All our tapes comply with European 2004/12/CE Packaging directive.

PAKAVIMO MEDŽIAGOS

PAKAVIMO ĮRANGA

PAKAVIMO PROCESŲ OPTIMIZAVIMAS

UAB „AIRUSLITA“
Ringuvos g. 53, LT-45245, Kaunas, Lietuva
Tel.: +370 37 7560556
El. paštas: info@packspace.lt
www.packspace.lt

J. k.: 235953170
PVM mok. kodas: LT359531716
Ofiso adresas: Partizanų g. 63M, LT-50306, Kaunas, Lithuania
Banko kodas: Luminor bank AB, kodas 21400
A/s Nr.: LT56 2140 0300 0410 0672